

# CYCOLAC<sup>™</sup> RESIN INP338

### **REGION AMERICAS**

# DESCRIPTION

SABIC INP338 is an ultra high rubber ABS impact modifier resin, and is based on polybutadiene rubber. Offers superior impact efficiency, especially at low temperatures. Reduces notch sensitivity when alloyed with engineering polymers. Disperses easily. Provides abrasion and chemical resistance to polymers. Provides toughness to PVC sheet, profile, electrical conduit and injection molded applications. Increases the impact strength of recycle PVC and other recyclates. Can be blended with polyurethanes and other polymers for improved performance and economics. Can be used to improve the impact performance of PC, polyesters, and CPVC. Powder. FDA compliant (part use must be at room temperature or below).

## TYPICAL PROPERTY VALUES

Revision 20181012

| PROPERTIES  | TYPICAL VALUES | UNITS                           | TEST METHODS             |
|---|----------------|---------------------------------|--------------------------|
| MECHANICAL  |                |                                 |                          |
| Hardness, Shore D                                 | 40             | -                               | ASTM D 2240              |
| PHYSICAL  |                |                                 |                          |
| Specific Gravity                                  | 0.95           | -                               | ASTM D 792               |
|   |                |                                 |                          |
| Melt Flow Rate, 200°C/3.8 kgf                     | 5.7            | g/10 min                        | ASTM D 1238              |
| Melt Flow Rate, 200°C/3.8 kgf<br>Density (Molded) | 5.7<br>0.96    | g/10 min<br>g/cm <sup>3</sup>   | ASTM D 1238<br>ISO 1183  |
|   |                | 0,                              |                          |
| Density (Molded)                                  | 0.96           | g/cm <sup>3</sup>               | ISO 1183                 |
| Density (Molded)<br>Mean Resin Particle Size      | 0.96           | g/cm <sup>3</sup><br>micrometer | ISO 1183<br>SABIC method |

#### DISCLAIMER

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.